Response to Office Action mailed March 21, 2007

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:** 

Claim 1 (Currently Amended): A user interface device that causes a user interface-related window to be displayed on a display unit, which is capable of displaying various pieces of

information, said user interface device comprising:

a command input module that receives a user command;

a storage module that stores at least data of a first manipulation menu display field,

data of a second manipulation menu display field, and data of a viewer display field for

displaying a processing object of each manipulation; and

a display control module that, when the user command received by said command

input module is a first manipulation window display command, reads the data of the first

manipulation menu display field and the data of the viewer display field from said storage

module and displays a first manipulation window, which includes the first manipulation menu

display field arranged at a predetermined location on a periphery of the viewer display field,

on said display unit and when the user command received by said command input module is a

second manipulation window display command, reads the data of the second manipulation

menu display field and the data of the viewer display field from said storage module and

displays a second manipulation window, which includes the second manipulation menu

display field arranged at a location different from opposite to the predetermined location on

the periphery of the viewer display field, on said display unit,

in the case of input of the second manipulation window display command during

display of the first manipulation window on said display unit, said display control module

sliding the first manipulation window to make the first manipulation menu display field

disappear from the display on said display unit and to make the second manipulation menu

display field appear on the display on said display unit, while making the viewer display field

Page 2 of 11

remain on the display on said display unit, so as to display the second manipulation window

on said display unit,

in the case of input of the first manipulation window display command during display

of the second manipulation window on said display unit, said display control module sliding

the second manipulation window to make the second manipulation menu display field

disappear from the display on said display unit and to make the first manipulation menu

display field appear on the display on said display unit, while making the viewer display field

remain on the display on said display unit, so as to display the first manipulation window on

said display unit.

Claim 2 (Original): A user interface device in accordance with claim 1, wherein the first

manipulation window has the first manipulation menu display field located on a left side or a

right side of the viewer display field,

the second manipulation window has the second manipulation menu display field

located on the right side or the left side of the viewer display field, and

said display control module slides the first manipulation window or the second

manipulation window leftward or rightward.

Claim 3 (Original): A user interface device in accordance with claim 1, wherein the first

manipulation window has the first manipulation menu display field located on an upper side

or a lower side of the viewer display field,

the second manipulation window has the second manipulation menu display field

located on the lower side or the upper side of the viewer display field, and

said display control module slides the first manipulation window or the second

manipulation window upward or downward.

Page 3 of 11

module stores a first manipulation window option bar corresponding to the first manipulation

window display command and a second manipulation window option bar corresponding to

the second manipulation window display command,

for display of the first manipulation window on said display unit, said display control

module arrays the first manipulation window option bar and the second manipulation window

option bar in an identical direction of an alignment of the viewer display field and the first

manipulation menu display field and displays the first manipulation window option bar longer

and the second manipulation window option bar shorter, and

for display of the second manipulation window on said display unit, said display

control module arrays the first manipulation window option bar and the second manipulation

window option bar in an identical direction of an alignment of the viewer display field and

the second manipulation menu display field and displays the second manipulation window

option bar longer and the first manipulation window option bar shorter.

Claim 5 (Original): A user interface device in accordance with claim 4, wherein said display

control module slides the first manipulation window option bar and the second manipulation

window option bar to change the longer side and the shorter side, when the first manipulation

window is slid to change over the display to the second manipulation window on said display

unit or when the second manipulation window is slid to change over the display to the first

manipulation window.

Page 4 of 11

Claim 6 (Original): A user interface device in accordance with claim 1, wherein the first

manipulation menu display field displays at least one of a menu, a guidance, and a data

setting input box relating to image editing,

the second manipulation menu display field displays at least one of a menu, a

guidance, and a data setting input box relating to image printing, and

the viewer display field displays an image as an object of the image editing or the

image printing.

Claim 7 (Original): A user interface device in accordance with claim 6, wherein the viewer

display field displays a captured image of a motion picture as the object of the image editing

or the image printing.

Claim 8 (Original): A user interface device in accordance with claim 7, said user interface

device being mounted on a printer, which connects with a disk recorder using a hard disc or a

digital versatile disc as a recording medium of motion pictures and has a function of capturing

a motion picture from the recording medium of the disk recorder.

Claim 9 (Original): A user interface device in accordance with claim 1, said user interface

device is a computer comprising said display unit, said command input module, said storage

module, and said display control module.

Page 5 of 11

Claim 10 (Original): A user interface display method by computer software that reads required data from a storage module, which stores at least data of a first manipulation menu display field, data of a second manipulation menu display field, and data of a viewer display field for displaying a processing object of each manipulation, and displays the required data on a display unit, said user interface display method comprising the steps of:

- (a) receiving a user command;
- (b) when the user command is a first manipulation window display command, reading the data of the first manipulation menu display field and the data of the viewer display field from said storage module and displaying a first manipulation window, which includes the first manipulation menu display field arranged at one side on periphery of the viewer display field, on said display unit;
- (c) when the user command is a second manipulation window display command, reading the data of the second manipulation menu display field and the data of the viewer display field from said storage module and displaying a second manipulation window, which includes the second manipulation menu display field arranged at the opposite side on the periphery of the viewer display field, on said display unit;
- (d) in the case of input of the second manipulation window display command during display of the first manipulation window on said display unit, sliding the first manipulation window to make the first manipulation menu display field disappear from the display on said display unit and to make the second manipulation menu display field appear on the display on said display unit, while making the viewer display field remain on the display on said display unit, so as to display the second manipulation window on said display unit; and
- (e) in the case of input of the first manipulation window display command during display of the second manipulation window on said display unit, sliding the second manipulation window to make the second manipulation menu display field disappear from the

display on said display unit and to make the first manipulation menu display field appear on

the display on said display unit, while making the viewer display field remain on the display

on said display unit, so as to display the first manipulation window on said display unit.

Claim 11 (Currently Amended): A user interface device that causes a user interface related

window to be displayed on a display unit, which is capable of displaying various pieces of

information in accordance with claim 1, said user interface device further comprising:

a reception module that receives a radio signal transmitted from a remote control unit,

in response to a press operation of one of Up, Down, Left, Right, and OK keys on said remote

control unit; and

a radio signal identification module that identifies the radio signal received by said

reception module as one of Up, Down, Left, Right, and OK commands;

a storage module that stores data for displaying at least a first manipulation window

and a second manipulation window on said display unit; and

a display control module that, wherein when the first manipulation window or the

second manipulation window is read from said the storage module and is displayed on said

the display unit, the display control module executes a setting on the displayed manipulation

window or a changeover of display to the other manipulation window, in response to one of

the Up, Down, Left, Right, and OK commands identified by said radio signal identification

module.

Claims 12-20 (Canceled).

Page 7 of 11